



## Technical Product Data

- a) Product Name **HIGHBUILD W TEXTURE**
- b) Reference Number PP45
- c) Product Description A high quality durable textured system based on an outstanding vinyl resin incorporating Titanium and Iron Oxide Pigments ensuring good colour retention. Various size particles of Granicalcium are used to give a long lasting finish for any Masonry Substrates.
- d) Uses A highbuild long life coating for Masonry & Exterior Plywood Substrates
- e) Pack Sizes 14 & 21 Kilo Drums
- f) Colour Range 6 colours plus White
- g) Specific Gravity 1.65
- h) Solids 74.2
- I) Spreading Rate 2.25kg- 3.00 kg Depending on Texture Finish & Substrate
- j) Drying Time Touch dry 12 hours Full cure 2-3 weeks
- k) Lowest application Temperature 5 degrees C.
- l) Dry Recommended Application Thickness 900 Microns
- m) Methods Of Application Roller+Trowel Roller+ Texturing Air spray Pressure Pot
- n) Preparation See Preparation Sheet 1.
- o) Storage Life One Year Frost Free Storage
- p) Thinner/Cleaner Water
- q) Safety Ensure the use of good filter masks when spraying, splashes in the eyes must be washed out at once with plenty of clean water. Barrier cream is recommended
- r) Storage Store in a frost free area, avoid high temperatures and direct sunlight.